

TRANSMITTAL LETTER TO THE UNITED STATES
DESIGNATED/ELECTED OFFICE (DO/EO/US)
CONCERNING A FILING UNDER 35 U.S.C. 371

6640/62669

U.S. APPLICATION NO. (if known, see 37 CFR 1.5)

09/807187

INTERNATIONAL APPLICATION NO.

PCT/JP00/05372

INTERNATIONAL FILING DATE

8/10/00

PRIORITY DATE CLAIMED

8/11/99

TITLE OF INVENTION

JC07 Rec'd PCT/PTO 10 APR 2001

~~MULTI-SIGNAL TRANSMITTING APPARATUS AND MULTI-CARRIER SIGNAL RECEIVING APPARATUS~~

APPLICANT(S) FOR DO/EO/US

ITO OFFICE LTD.

Applicant herewith submits to the United States Designated/Elected Office (DO/EO/US) the following items and other information:

1. ☒ This is a **FIRST** submission of items concerning a filing under 35 U.S.C. 371.
2. ☐ This is a **SECOND** or **SUBSEQUENT** submission of items concerning a filing under 35 U.S.C. 371.
3. ☒ This express request to begin national examination procedures (35 U.S.C. 371(f)) at any time rather than delay examination until the expiration of the applicable time limit set in 35 U.S.C. 371(b) and PCT Articles 22 and 39(1).
4. ☐ A proper Demand for International Preliminary Examination was made by the 19th month from the earliest claimed priority date.
5. ☒ A copy of the International Application as filed (35 U.S.C. 371(c)(2))
 - a. ☒ is transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ has been transmitted by the International Bureau.
 - c. ☐ is not required, as the application was filed in the United States Receiving Office (RO/US).
6. ☒ A translation of the International Application into English (35 U.S.C. 371(c)(2)).
7. ☒ Amendments to the claims of the International Application under PCT Article 19 (35 U.S.C. 371(c)(3))
 - a. ☐ are transmitted herewith (required only if not transmitted by the International Bureau).
 - b. ☐ have been transmitted by the International Bureau.
 - c. ☒ have not been made; however, the time limit for making such amendments has NOT expired.
 - d. ☐ have not been made and will not be made.
8. ☐ A translation of the amendments to the claims under PCT Article 19 (35 U.S.C. 371(c)(3)).
9. ☐ An oath or declaration of the inventor(s) (35 U.S.C. 371(c)(4)).
10. ☐ A translation of the annexes to the International Preliminary Examination Report under PCT Article 36 (35 U.S.C. 371(c)(5)).

Items 11. to 16. below concern document(s) or information included:

11. ☐ An Information Disclosure Statement under 37 CFR 1.97 and 1.98.
12. ☐ An assignment document for recording. A separate cover sheet in compliance with 37 CFR 3.28 and 3.31 is included.
13. ☐ A **FIRST** preliminary amendment.
☐ A **SECOND** or **SUBSEQUENT** preliminary amendment.
14. ☐ A substitute specification.
15. ☐ A change of power of attorney and/or address letter.
16. ☐ Other items or information:

1. Formal Drawings 13 Figures 11 Sheets
2. Copy of Search Report and its English translation

17. ☒ The following fees are submitted:

BASIC NATIONAL FEE (37 CFR 1.492 (a) (1) - (5)) :

Neither international preliminary examination fee (37 CFR 1.482)
nor international search fee (37 CFR 1.445(a)(2)) paid to USPTO
and International Search Report not prepared by the EPO or JPO \$970.00

International preliminary examination fee (37 CFR 1.482) not paid to
USPTO but International Search Report prepared by the EPO or JPO \$860.00

International preliminary examination fee (37 CFR 1.482) not paid to USPTO but
international search fee (37 CFR 1.445(a)(2)) paid to USPTO \$690.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
but all claims did not satisfy provisions of PCT Article 33(1)-(4) \$670.00

International preliminary examination fee paid to USPTO (37 CFR 1.482)
and all claims satisfied provisions of PCT Article 33(1)-(4) \$96.00

ENTER APPROPRIATE BASIC FEE AMOUNT =

CALCULATIONS PTO USE ONLY

JC08 Rec'd PCT/PTO 10 APR 2001

\$ 860.00

Surcharge of \$130.00 for furnishing the oath or declaration later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(e)).

\$

CLAIMS	NUMBER FILED	NUMBER EXTRA	RATE
Total claims	9 - 20 =		X \$ 20.00
Independent claims	4 - 3 =	1	X \$ 80.00

\$

\$80.00

MULTIPLE DEPENDENT CLAIM(S) (if applicable)

+ \$260.00

\$

TOTAL OF ABOVE CALCULATIONS =

\$

Reduction of 1/2 for filing by small entity, if applicable. A Small Entity Statement
must also be filed (Note 37 CFR 1.9, 1.27, 1.28).

\$

SUBTOTAL =

\$940.00

Processing fee of \$130.00 for furnishing the English translation later than ☐ 20 ☐ 30
months from the earliest claimed priority date (37 CFR 1.492(f)).

\$

TOTAL NATIONAL FEE =

\$

Fee for recording the enclosed assignment (37 CFR 1.21(h)). The assignment must be
accompanied by an appropriate cover sheet (37 CFR 3.28, 3.31). \$40.00 per property

\$

TOTAL FEES ENCLOSED =

\$ 940.00

Amount to be
refunded:

\$

charged:

\$

a. ☒ A check in the amount of \$ 940.00 to cover the above fees is enclosed.

b. ☐ Please charge my Deposit Account No. _____ in the amount of \$ _____ to cover the above fees.
A duplicate copy of this sheet is enclosed.

c. ☒ The Commissioner is hereby authorized to charge any additional fees which may be required, or credit any
overpayment to Deposit Account No. 03-3125. A duplicate copy of this sheet is enclosed.

NOTE: Where an appropriate time limit under 37 CFR 1.494 or 1.495 has not been met, a petition to revive (37 CFR
1.137(a) or (b)) must be filed and granted to restore the application to pending status.

SEND ALL CORRESPONDENCE TO:

Jay H. Maioli, Esq.
Cooper & Dunham LLP.
1185 Avenue of the Americas
New York, New York 10036
Tel: 212-278-0400
Fax: 212-391-0525

SIGNATURE:

Jay H. Maioli

NAME

27,213

REGISTRATION NUMBER

DOCUMENT PROCESSING

13/PRTS

09/807187

JC08 Rec'd FCT/PTO 10 APR 2001

DESCRIPTION

MULTI-CARRIER SIGNAL TRANSMITTING APPARATUS AND MULTI-CARRIER
SIGNAL RECEIVING APPARATUS

TECHNICAL FIELD

The present invention relates to a multi-carrier signal transmitting apparatus and a multi-carrier signal receiving apparatus preferable for application to a case of transmitting multi-carrier signals by radio.

BACKGROUND ART

Recently, OFDM (Orthogonal Frequency Division Multiplex: orthogonal frequency division multiplexing) system has been employed as a transmission system highly resistant to multi-pass interference as well as having an excellent frequency use efficiency. According to this OFDM system, a plurality of carriers (hereinafter referred to as sub-carrier) orthogonal to each other are disposed at every predetermined frequency interval within a single transmission band and data is distributed to respective sub-carriers and modulated for transmission. According to this system, its transmission apparatus disposes transmission data obtained in time series virtually on a frequency axis, allocates transmission data to each sub-carrier, and orthogonally transforms it to multi-carrier signals at the predetermined frequency interval by reverse fast Fourier transformation or the like. A receiving apparatus thereof converts received multi-carrier signal

inversely to transmission time to data secured in time series so as to obtain reception data.

FIG. 1 is a diagram showing an example of the structure of a radio transmission apparatus according to the OFDM system. Hereinafter, the structure will be described. Here, a radio transmission apparatus 100 comprises a video circuit 101 and a voice circuit 102 and the respective circuits 101, 102 carries out processing for encoding the inputted video signal and voice signal. For example, the video circuit 101 performs encoding according to irreversible image compression encoding method such as a processing for converting animation video signal to MPEG (Moving Picture Experts Group) system image data, a processing for converting static image video signal to JPEG (Joint Photographing coding Experts Group) system image data. Or encoding with reversible image compression method like JBIG (Joint Bi-level Image Experts Group) is permissible. A voice circuit 102 carries out encoding based on the MPEG audio method, CELP (Code Excited Linear Prediction) method, PCM (Pulse Code Modulation) method or the like. In the meantime, the coded data may be provided with ECC (Error Correcting Code) such as the Reed-Solomon code, the turbo code and the like.

Video data outputted by a video circuit 101 and voice data outputted by the voice circuit 102 are supplied to a mixing circuit 103 in which they are converted to single-system data. After that, it is supplied to an interleaver 104, in which

interleave processing is carried out by changing data arrangement to disperse bit series. Data interleaved by the interleaver 104 is subjected to modulation processing by a modulator 105. In this modulator 105, first, a preamble signal is inserted into the bit sequence and next, as a primary modulation, for example, DQPSK modulation (Differential Quadrature Phase Shift keying) is carried out. In the meantime, other modulation method than the DQPSK modulation may be employed such as QPSK, BPSK, 8PSK, QAM and the like.

Data primarily modulated by the modulator 105 is supplied to a reverse fast Fourier transformation circuit (IFFT circuit) 106 and as a secondary modulation, reverse Fourier transformation processing for converting data disposed on time axis to data arrangement on the frequency axis by arithmetic processing of reverse Fourier transformation is carried out and further, window application processing is carried out by multiplying window data. If the reverse Fourier transformation processing is carried out in this IFFT circuit 106, a transmission symbol stream disposed on the frequency axis virtually up to then is averaged so as to be transmission series. In the IFFT circuit, each time when data of a predetermined unit is inputted, reverse Fourier transformation arithmetic processing is carried out for that inputted data. In this specification, time for carrying out the arithmetic processing of this one unit is called single modulation time.

Output of the IFFT circuit 106 is supplied to a digital/analog converter 107 so as to be converted to analog signal. After the conversion, the analog signal is supplied to a high-frequency portion (RF portion) 108, in which high-frequency processing such as filtering, frequency conversion are carried out so as to gain a transmission signal of a predetermined transmission channel. After that, it is transmitted by radio through an antenna 110. Processing timing in each circuit in the radio transmission apparatus 100 is controlled by a time base controller (TBC) 109.

FIG. 2 is a diagram showing a radio reception apparatus for receiving a signal transmitted from the radio transmission apparatus 100 shown in FIG. 1. Hereinafter, the structure thereof will be described. The radio reception apparatus 200 supplies a signal received by an antenna 201 to a high-frequency portion (RF portion) 202 so as to carry out such reception processing as filtering and frequency conversion. Consequently, a reception signal of a predetermined channel is obtained. This reception signal is supplied to the analog/digital converter 203 and converted to digital data. Reception series subjected to digital conversion is supplied to a window detecting portion 204. This window detecting portion 204 carries out processing for detecting synchronism by detecting a break in data to be subjected to Fourier transformation based on window data multiplied by the transmission system from reception series.

Output of the window detecting portion 204 is supplied to the fast Fourier transformation circuit (FFT circuit) 205 and transformation processing is carried out, in which Fourier transformation action is carried out at the timing of the break in data detected by the window detecting portion 204 and data on the frequency axis is converted to data arrangement on time axis by the arithmetic processing of the Fourier transformation. The reception series Fourier transformed is supplied to a decoder 206, in which decoding processing for returning conversion processing applied at the time of transmission such as the DQPSK modulation is carried out so as to generate a reception symbol stream.

This reception symbol stream is supplied to a deinterleaver 207, in which deinterleave processing for returning bit series dispersed by interleave processing at the time of transmission to its original data arrangement is carried out so as to obtain reception encoding bit series. This reception encoding bit series is supplied to a viterbi decoder 208 and converted to reception information bit series by viterbi decoding processing. Video information in the converted reception information bit series is supplied to a video circuit 209 and voice information is supplied to a voice circuit 210.

In the video circuit 209, data encoded by the video circuit 101 of the transmission system is decoded so as to obtain transmitted video data. In the voice circuit 210, data

encoded by the voice circuit 102 of the transmission system is decoded so as to obtain transmitted voice data. Processing timing in each circuit in the radio reception apparatus 200 is controlled by a time base controller (TBC) 211.

With the above described structure, transmission and reception of the OFDM system signal are carried out. The primary modulation by the modulator 105 at the time of transmission is a modulation system in which the phase of carrier is changed in discrete manner depending on transmission data, so that it has a large advantage in frequency application efficiency. Because, in the reverse Fourier transformation processing in the IFFT circuit 106, the bit series disposed on the subcarrier is averaged on time axis, it has such a large advantage that it is highly resistant to interfering wave such as fading and shadowing.

However, on the side receiving such multi-carrier signal, respective bit series cannot be decoded until Fourier transformation processing in the FFT circuit 205 is carried out. If a break for one modulation (hereinafter referred to break) is not recognized properly when the FFT circuit 205 executes the Fourier transformation processing at the time of reception, accurate bit series cannot be decoded.

To achieve proper Fourier transformation action in the FFT circuit, it is necessary to determine the break depending on a power level of transmission data because the break (

hereinafter referred to as break) of one modulation time cannot be determined from data received in a circuit on a prestage of the Fourier transformation circuit (window detecting portion 204 in FIG. 2). Ordinarily, for the known preamble signal contained in the transmission data, correlation in power level is obtained. In order to increase the accuracy of correlation value to be obtained here, calculation is necessary without reducing the bit width of each channel. For the reason, there is a problem that the scale of a circuit for detecting the correlation is increased.

DISCLOSURE OF THE INVENTION

The present invention has been achieved in views of problems in the above described radio transmission of the multi-carrier signal and an object of the present invention is to enable demodulation by determining a break of one modulation unit with a simple structure or processing prior to Fourier transformation on the side receiving a signal to be transmitted as a multi-carrier signal.

According to a first invention, there is provided a multi-carrier signal transmission apparatus for transmitting a signal in which first information necessary for gaining synchronism of transmission signal is disposed at a predetermined interval in second information which is the other information, comprising: data arrangement means for arranging the first information and the second information; first

modulation means for generating a transmission symbol stream by modulating data created by the data arrangement means; symbol generating means for expanding a transmission symbol stream generated by the first modulation means on frequency axis so as to generate the transmission symbol stream symmetrical on the frequency axis; and second modulation means for converting the transmission symbol stream symmetrical on the frequency axis generated on the symbol generating means by reverse Fourier transformation.

Consequently, first information necessary for gaining synchronism is contained in transmission symbol disposed symmetrically with respect to a reference position on frequency axis. As a result, the side receiving a signal transmitted from this apparatus is capable of extracting only any one of real number portion and imaginary number portion of the first information.

According to a second invention, there is provided a multi-carrier signal transmission apparatus according to the first invention wherein the data arrangement means disposes the first information and the second information alternately.

Consequently, when self correlation of the first information is carried out in a reception circuit, a more highly accurate correlation value can be produced.

According to a third invention, there is provided a multi-carrier signal transmission apparatus according to the

first invention wherein with a symbol at the reference frequency position of the transmission symbol stream as the center, the symbol generating means expands respective symbols of the transmission symbol stream other than that symbol symmetrically on the frequency axis.

Consequently, symbols are arranged symmetrically on the frequency axis centering on a frequency position which serves as reference like 0 kHz and the like, so that the symbols can be expanded symmetrically on the frequency axis favorably.

According to a fourth invention, there is provided a multi-carrier signal reception apparatus for receiving multi-carrier signal including first information necessary for gaining synchronism of transmission signal and second information, comprising: memory means for memorizing any one of a real number portion and an imaginary number portion in the first information; delay means for delaying a received symbol stream by a predetermined time; a filter portion for extracting the first information using a reception symbol stream delayed by the delay means and a reception symbol stream not delayed; a correlator for gaining correlation between an output of the filter portion and the first information of the real number portion or imaginary number portion memorized in the memory means; and determining means for detecting synchronism depending on a peak position of a correlation value of the correlator.

Consequently, when symbols disposed symmetrically with

respect to the reference position on the frequency axis are received, by gaining correlation between first information extracted from that received symbol and preliminarily prepared first information, only a correlation value of any one of the real number portion and the imaginary number portion is detected when its correlation is detected. Thus, as the first information which should be prepared preliminarily for detection of the correlation within the reception apparatus, only any one of the real number portion and the imaginary number portion has to be prepared. As a result, the amount of the first information prepared in the reception apparatus can be reduced correspondingly and a processing amount for detecting the correlation can be reduced, so that information for gaining synchronism contained in the received multi-carrier signal can be detected prior to Fourier transformation with simple structure and simple processing.

According to a fifth invention, there is provided a multi-carrier signal reception apparatus according to the fourth invention wherein when processing time of a single unit for Fourier-transforming the multi-carrier signal is a single modulation time, a predetermined time to be delayed by the delay means is set to $1/2$ a single modulation time.

Consequently, only the first information necessary for gaining synchronism can be extracted easily from the transmission symbol in which the first information and the

second information are arranged alternately.

According to a sixth invention, there is provided a multi-carrier signal transmission apparatus for transmitting first information necessary for gaining synchronism of transmission signal and second information which is the other information as the multi-carrier signal, comprising: first modulation means for generating a transmission symbol stream by the first information and a transmission symbol stream by the second information selectively; and symmetrical transmission symbol stream generating means in which a transmission symbol stream based on the first information generated by the first modulation means is the transmission symbol stream expanded symmetrically on frequency axis with respect to a predetermined frequency position.

Consequently, transmission of the transmission symbol stream composed of the first information necessary for gaining synchronism and transmission of the transmission symbol stream composed of the second information which is the other information can be carried out selectively. Thus, when transmitting an asynchronous packet, it is possible to transmit the symbol stream composed of the first information symmetrically on a reference frequency position at a head slot and then transmit just the symbol stream composed of the second information at a next slot, thereby enabling information necessary for gaining synchronism to be transmitted effectively.

According to a seventh invention, there is provided a multi-carrier signal transmission apparatus according to the sixth invention wherein with a symbol at the reference frequency position of the transmission symbol stream as the center, the first modulation means expands respective symbols of the transmission symbol stream other than that symbol symmetrically on the frequency axis.

Consequently, with a reference frequency position like 0 kHz as the center, symbols are arranged symmetrically on the frequency axis, so that the symbols can be expanded symmetrically on the frequency axis favorably.

According to an eighth invention, there is provided a multi-carrier signal reception apparatus for receiving the first information necessary for gaining synchronism of a transmission signal and second information which is the other information, comprising: memory means for memorizing the first information; correlator for gaining correlation between the received symbol stream and the first information of the real number portion or imaginary number portion memorized in the memory means; and determining means for detecting synchronism depending on a peak position of a correlation value of the correlator.

Consequently, when receiving the symbol stream composed of the first information, a correlation value is detected from only any one of the real number portion and the imaginary number portion contained in that reception symbol. Therefore, as the

first information to be preliminarily prepared for detection of the correlation within the reception apparatus, only any one of the real number portion and the imaginary number portion has to be prepared, so that the amount of the first information prepared within the reception apparatus can be reduced correspondingly and further, the processing amount for detecting the correlation can be reduced. Thus, information for gaining synchronism contained in the received multi-carrier signal can be detected prior to Fourier transformation by simple structure and simple processing.

According to a ninth invention, there is provided a multi-carrier signal reception apparatus according to the eighth invention wherein the memory means memorizes only any one of the real number portion and the imaginary number portion in said first information.

Consequently, information for gaining synchronism contained in the reception symbol can be detected easily using storage information having a small information amount.

BRIEF DESCRIPTION OF DRAWINGS

FIG. 1 is a block diagram showing an example of a transmission system for a multi-carrier signal.

FIG. 2 is a block diagram showing an example of a reception system for the multi-carrier signal.

FIG. 3 is a block diagram showing an example of a transmission system according to a first embodiment of the

present invention.

FIG. 4 is an explanatory diagram showing an example of a transmission symbol stream according to a first embodiment of the present invention.

FIG. 5 is an explanatory diagram showing an example of the transmission symbol stream expanded according to the first embodiment of the present invention.

FIG. 6 is a block diagram showing an example of a preamble signal detecting structure according to a first embodiment of the present invention.

FIG. 7 is a waveform diagram showing an example of waveforms in I channel and Q channel of preamble contained in an expanded transmission symbol stream.

FIG. 8 is an explanatory diagram showing an example of a transmission state according to a second embodiment of the present invention.

FIG. 9 is an explanatory diagram showing an example of a transmission symbol stream according to a second embodiment of the present invention.

FIG. 10 is an explanatory diagram showing an example of the transmission symbol stream expanded according to the second embodiment of the present invention.

FIG. 11 is a block diagram showing an example of a preamble signal detecting structure according to the second embodiment of the present invention.

FIG. 12 is a flow chart showing an example of preamble signal detecting processing according to the second embodiment of the present invention.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, a first embodiment of the present invention will be described with reference to FIGS. 3-7.

In this embodiment, the present invention is applied to a case of carrying out radio transmission of a multi-carrier signal. FIG. 3 shows an example of the structure of a transmission apparatus of this embodiment. Hereinafter, the structure will be described. A radio transmission apparatus 100' comprises a video circuit 101 and a voice circuit 102, and the respective circuits 101, 102 carry out processing for encoding an inputted video signal and voice signal. Video data outputted by the video circuit 101 and voice data outputted by the voice circuit 102 are supplied to a mixing circuit 103 so as to turn to single-system data. After that, this data is supplied to an interleaver 104, which carries out interleave processing in which bit series is diffused by changing an data arrangement. Data interleaved by the interleaver 104 is modulated by a modulator 105 for the purpose of transmission. This modulator 105 inserts a preamble signal into a bit series and then carries out DQPSK modulation (or modulation by other modulation methods such as QPSK, BPSK, 8PSK, QAM) as the primary modulation so as to obtain a symbol stream as modulation output.

FIG. 4 shows an example of the symbol stream outputted by the modulator 105. In FIG. 4, the frequency axis is indicated virtually in the form of an abscissa axis, in which 24 pieces of symbols are expressed in a unit. This unit of the symbol column is modulated to a multi-carrier signal by means of a circuit described later. In this structure, 24 pieces of symbols S_1 - S_{24} are disposed at predetermined frequency intervals ($f_s = 4.17$ kHz) between 0 kHz and 100 kHz, while the symbols S_1 , S_{24} (that is, a symbol located at 0 kHz and a symbol located at 100 kHz) located on both ends of the 24 symbols S_1 - S_{24} serve for guard carriers so that they do not carry anything. Remaining 22 symbols S_2 - S_{23} are divided to symbols for use for transmitting first information and symbols for use for transmitting second information. The first information is a preamble signal. The second information is data desired to be transmitted actually (for example, data obtained by encoding the video signal or voice signal). In the meantime, a band from 0 kHz to 100 kHz is called a base band range.

As for disposition of the first information symbol and the second information symbol, the first information symbol and the second information symbol are disposed alternately. That is, as shown in FIG. 4, the symbols S_2 , S_4 , S_6 , S_8 , S_{10} , S_{12} , S_{14} , S_{16} , S_{18} , S_{20} , S_{22} are disposed as symbols for transmitting (modulating) the first information S_1 and the symbols S_3 , S_5 , S_7 ,

$S_9, S_{11}, S_{13}, S_{15}, S_{17}, S_{19}, S_{21}, S_{23}$ are disposed as symbols for transmitting (modulating) the second information D2. The symbol column shown in FIG. 4 is a symbol column to be processed in a single modulation time at the time of modulation to multi-carrier signals and here, called a symbol column in the unit of a single modulation.

According to this embodiment, data modulated primarily by the modulator 105 is supplied to a symbol expanding portion 111. This symbol expanding portion 111 expands only the first information of the symbol column in the unit of a single modulation symmetrically on the frequency axis. That is, when the symbol column disposed from 0 kHz to 100 kHz virtually on the frequency axis is inputted to the symbol expanding portion 111 as shown in FIG. 4, the symbols are expanded symmetrically on the frequency axis with the position of 0 kHz as a reference frequency position so that this reference position serves as a central position.

FIG. 5 is a diagram showing an expanded state. With the symbol S_1 disposed virtually at 0 kHz which is a reference position acting as a guard carrier in the center, the symbols S_2-S_{24} are expanded symmetrically vertically on the frequency axis (to the right and left in a state shown in FIG. 5), such that the symbols are disposed at a predetermined frequency interval f_s in a range from -100 kHz to 100 kHz. Therefore, in the symbol developing portion 111, the symbol S_1 at the center

position (reference position) is kept as it is while as of the other symbols S_2 - S_{24} , even symbols S_2 , S_4 , S_6 , S_8 , ... S_{22} are expanded in an opposite direction. That is, assuming that the frequency position of the symbol in which the first information is disposed in the order of the frequency from -100 kHz is $-f_{11}$, $-f_{10}$, $-f_9$, ... $-f_1$, f_1 , ... f_9 , f_{10} , f_{11} , as the symbols at frequency positions $-f_1$ - $-f_{11}$ lower than the reference position (0 Hz), the symbols S_2 , S_4 , ... S_{22} are disposed in order from a higher frequency position. As the symbols at frequency positions f_1 - f_{11} higher than the reference position, the symbols S_2 , S_4 , ... S_{22} are disposed in order from a lower frequency position, so that they are inverted in terms of the right and left direction with 0 Hz as a border on the frequency axis.

Returning to the description of FIG. 3, a symbol stream outputted from the symbol developing portion 111 having such an arrangement is supplied to a reverse fast Fourier transformation circuit (IFFT circuit) 106 and in a secondary modulation, data disposed on a time axis is subjected to reverse Fourier transformation processing so as to convert it to a data arrangement on the frequency axis by arithmetic processing of reverse Fourier transformation. Further, the window application processing for multiplying this result by window data is carried out. If the reverse Fourier transformation processing is carried out by this IFFT circuit 106, the transmission symbol

stream disposed virtually on the frequency axis up to here is averaged on a time axis so that it becomes transmission series. Data of a single modulation unit processed in a single modulation time in this IFFT circuit 106 is a symbol column disposed virtually in a range from -100 kHz to 100 kHz as shown in FIG. 5.

An output of the IFFT circuit 106 is supplied to a digital/analog converter 107 and converted to an analog signal. That converted analog signal is supplied to a high-frequency portion (RF portion) 108 so as to carry out high frequency processing such as filtering and frequency conversion to obtain a transmission signal of a predetermined transmission channel. After that, it is transmitted by radio from an antenna 110. Processing timing in each circuit in the radio transmission apparatus 100 is controlled by a time base controller (TBC) 109.

Next, a radio receiving apparatus for receiving a multi-carrier signal transmitted by radio under the structure shown in FIG. 3 will be described. According to this embodiment, the basic structure for conducting receiving processing is the same as the structure of the radio receiving apparatus 200 shown in FIG. 2. The multi-carrier signal received here is subjected to a processing for converting symbols disposed on the frequency axis by the fast Fourier transformation circuit (FFT circuit) to symbols on the time axis. A prestage circuit (window detecting

portion 204 shown in FIG. 2) for transformation processing by the FFT circuit determines a break of reception data and the determined break data is supplied to the FFT circuit (or circuit for controlling processing timing in the FFT circuit).

According to this embodiment, to determine a break of this reception data, a detection circuit having a structure shown in FIG. 6 is composed within a circuit disposed at a prestage of the FFT circuit so as to detect a preamble signal contained in the reception data. A circuit shown in FIG. 6 is a circuit to be incorporated in the window detecting portion 204 in the receiving apparatus shown in FIG. 2. If the reception series is obtained by an input terminal 11, a signal in which this reception series is delayed by a delay circuit 12 and a signal in which it is not delayed (that is, just a signal obtained in the input terminal 11) are supplied to a subtractor 13 so as to carry out subtraction processing. A delay circuit 12 is a circuit for delaying the single modulation time of the reception series by only $1/2$. Here, the single modulation time is assumed to be $240\mu\text{seconds}$ and a delay processing is carried out by the delay circuit 12 for $120\mu\text{seconds}$.

Carrying out of subtraction processing for the signal delayed by $1/2$ modulation time and the not delayed signal by means of the subtractor 13 functions as a comb filter for extracting only the preamble signal from signal transmitted with the state shown in FIG. 5. The delay time in the delay circuit

12 composing this filter is set based on the disposition of the first information symbol and the second information symbol.

The preamble signal extracted by the subtractor 13 is supplied to a shift register 14. The shift register 14 is a register in which 11-symbol data are set. A preamble buffer 15 stores the preamble data of the 11 symbols preliminarily. Correlation between data set in the shift register 14 and data stored preliminarily in the preamble buffer 15 is obtained by individual multipliers 16a, 16b, ... 16n for each symbol value. According to this embodiment, transmitted symbol data is symbol data subjected to DQPSK modulation. The DQPSK modulated symbol data is composed of I channel (real number portion which is an in-phase component of an orthogonal modulated wave) and Q channel (imaginary number portion which is an orthogonal component of the orthogonal modulated wave). Data of only the I channel which is a real number portion is stored in the preamble buffer 15, so that only data of the I channel is compared in the multipliers 16a, 16b, ... 16k.

Then, output of the correlation value of the respective multipliers 16a-16k is supplied to an accumulative adder 17, in which an electric power level corresponding to 11 symbols are added accumulately and output of the added values is supplied to a determining portion 18. The determining portion 18 carries out a processing for determining whether the electric power level obtained by accumulated addition is higher or lower than a

threshold level set preliminarily. If it is determined that it is higher than the threshold level, its determining output is supplied from a terminal 19 to a reception timing control means (circuit corresponding to a time base controller 211 of FIG. 2) and then, processing timing in the FFT circuit and the like is controlled based on the determined timing.

Here, a principle that the preamble signal can be detected by detecting correlation by means of a circuit shown in FIG. 6 will be described. Because modulation processing carried out on a received signal at this time, namely modulation in the modulator 105 within the radio transmission apparatus 100 is DQPSK modulation, it is data indicated by a position on a circle on the orthogonal coordinate axes formed by intersecting the I channel and the Q channel. In the modulator 105 on the transmission side, as the second information shown in FIG. 4, any one of these four points is selected. The first information is absolutely modulated such that all are at the same phase positions.

Assuming that the basic waveform of each subcarrier in the I channel is $\cos(2\pi f t)$ and the basic waveform of each subcarrier in the Q channel is $\sin(2\pi f t)$, of two outputs (I channel and Q channel), transmission power on one side (for example, I channel) is doubled because the component of the frequency f_n and the component of the frequency $-f_n$ (for example, component of the frequency f_1 and component of the

frequency $-f_1$ in FIG. 5) strengthen each other in the output of the high frequency portion 108 of the radio transmission apparatus 100'. If this is expressed by an equation, it can be expressed as follows.

$$\begin{aligned} \text{I component} &= \sum [\cos(2\pi f_1 t) + \cos \{2\pi(-f_1)t\}] \\ &= 2 \sum [\cos(2\pi f_1 t)] \quad \dots [1] \end{aligned}$$

On the other hand, in transmission power in the Q channel, its plus component and minus component kill each other so that the transmission power becomes 0. If this is expressed by an equation, it can be expressed as follows.

$$\text{Q component} = \sum [\sin(2\pi f_1 t) + \sin \{2\pi(-f_1)t\}] \quad \dots [2]$$

This is expressed by a waveform diagram in FIG. 7. An example of a carrier in the I channel of a subcarrier at a position $-f_1$ shown in FIG. 5 is shown in FIG. 7A and a carrier in the Q channel of a subcarrier in the Q channel at a position f_1 shown in FIG. 5 is shown in FIG. 7B. By adding the waveforms shown in FIGS. 7A, 7B for each channel, it is evident that the levels in the I channel strengthen each other while they kill each other in the Q channel. Thus, with the structure shown in FIG. 6, by memorizing only the preamble signal of one channel (I channel here) in the preamble buffer 15 and then obtaining correlation in reception power of the preamble signal, the preamble signal can be detected accurately.

If comparing a processing at the detection circuit of FIG. 6 with a processing at the conventionally same preamble

signal detecting circuit, the output of a filter (circuit corresponding to the subtractor 13 shown in FIG. 6) for extracting the preamble signal is expressed by $A + jB$ where the value of the real number portion (I channel) is A while the value of the imaginary number portion (Q channel) is jB . On the other hand, when the real number value C and the imaginary number value jD of the preamble signal are memorized in the preamble buffer, arithmetic operation of this memorized value $C + jD$ and the filter output value $A + jB$ is expressed by a following equation.

$$(A + jB) * (C + jD) = (AC - BD) + j(AD + BC) \quad \dots[3]$$

Although the arithmetic operation of the equation [3] is a processing in the conventional detecting circuit, in the detecting circuit of this embodiment, memorized data in the preamble buffer 15 may be C alone. If correlation detecting processing is expressed, it is expressed by a following equation.

$$(A + jB) * C = AC + jBC \quad \dots[4]$$

Therefore, it is possible to omit two multiplication processing and two addition/subtraction processing for each preamble of a symbol. In the signal structure described up to now, because there are provided 11 symbols of the preamble signals are provided, the multiplication processing of 22 pieces and addition/subtraction processing of 22 pieces can be omitted. Consequently, the structure of the preamble signal detecting

another circuit such as an adder so as to function as a filter.

Next, a second embodiment of the present invention will be described with reference to FIGS. 8-12.

In this embodiment also, the present invention is applied to a case for radio transmission of the multi-carrier signal. The basic structures of its transmission apparatus and reception apparatus are the same as those described in the first embodiment. After the transmission symbol stream generated by the primary modulator at the time of transmission is expanded in the symbol expanding portion, it is converted to the multi-carrier signal by means of the IFFT circuit (reverse fast Fourier transformation circuit). This embodiment is an example suitable for carrying out packet communication such as ATM (Asynchronous Transfer Mode) or the like. That is, as shown in FIG. 8, packets P1, P2, P3 composed of time slots TS1, TS2, TS3 are transmitted as required. Here, a time slot has the length of a modulation time.

Processing capacity of the IFFT circuit provided in the transmission apparatus is equal to capacity capable of processing signals (subcarrier interval $f_s = 4.17$ kHz) of -200 kHz $- 200$ kHz in terms of base band and when the width of 100 kHz is assumed to be a channel, it comes that processing capacity corresponding to four channels is provided.

At the time slot TS1 at the head of each packets P1, P2, P3, the preamble signal is sent and then, at the second and

third time slots, other signals (signal corresponding to the second information in the first embodiment) are sent.

According to this embodiment, the transmission symbol stream primarily modulated by DQPSK modulation in the modulator 105 within the transmission apparatus has the structure shown in FIG. 9. That is, when 24 pieces of symbols $S_1 - S_{24}$ are disposed virtually on the frequency axis at 4.17 kHz, as for the frequency position, the frequency position of the symbol S_1 is 100 kHz while the frequency position of the symbol S_{24} is 200 kHz. In this example also, symbols S_1, S_{24} (that is, symbol located at 100 kHz and symbol located at 200 kHz) on both ends of 24 symbols $S_1 - S_{24}$ serve for guard carriers, so that actually anything is not transmitted. Remaining 22 symbols $S_2 - S_{23}$ are symbols for use for transmitting the first information (that is, preamble signal) through the head time slot TS1.

Then, the preamble signal having the structure shown in FIG. 9 is expanded by the symbol expanding portion. At the time of expansion, with 0 kHz as a reference position (that is, central position), processing for expanding symmetrically on the frequency axis is carried out. FIG. 10 is a diagram showing an example of symbols to be expanded in this case. As shown in the same Figure, the 24 symbols $S_1 - S_{24}$ disposed virtually from 100 kHz to 200 kHz are disposed from -200 kHz to -100 kHz. Because they are disposed symmetrically with respect to 0 kHz, the

arrangements of the symbols are reverse to each other.

Such expansion in the symbol expanding portion is carried out in only the time slot TS1 for transmitting the preamble signal which is information required to be determined before decoding in this example and symbols in a time slot period for transmitting other information (second information) are not expanded. Then, the symbol stream processed in this way is supplied to the IFFT circuit and subjected to reverse Fourier transformation processing in which a time axis is converted to a frequency axis for every symbol in the modulation unit. A transformation output of the IFFT circuit is supplied to a high-frequency portion and transmitted by radio in a predetermined transmission frequency band.

As a result of such transmission, only the I channel component of the preamble signal is doubled as compared to a case where the transmission power level is not subjected to expansion processing. A principle that the transmission power level doubles is the same as the transmission principle described in the first embodiment and therefore, a description thereof is omitted.

Next, a radio receiving apparatus for receiving a signal transmitted in this way will be described. The basic structure of the reception apparatus is the same as the reception apparatus described in the first embodiment. This embodiment has a different structure for detecting the preamble signal

contained in a reception signal. The FFT circuit for transforming the multi-carrier signal is provided with a processing capacity corresponding to four channels like the IFFT circuit provided in the transmission apparatus.

FIG. 11 shows the structure of the preamble signal detecting circuit of a reception apparatus of this embodiment. Hereinafter, the structure thereof will be described. If a reception column is received by an input terminal 21, this reception column is supplied to a shift register 22. The shift register 22 is a register in which data of 22 symbols is set. The preamble buffer 23 stores preamble data of 22 symbols preliminarily (FIG. 11 is a diagram in which part thereof is omitted and the registers and buffers are not expressed with 22 stages).

Then, correlation between data set in the shift register 22 and data preliminarily accumulated in the preamble buffer 23 is obtained by individual multipliers 24a, 24b, ... 24n for each symbol. According to this embodiment, transmitted symbol data is symbol data subjected to DQPSK modulation. The DQPSK modulated symbol data is composed of I channel (real number portion which is an in-phase component of an orthogonal modulated wave) and Q channel (imaginary number portion which is an orthogonal component of the orthogonal modulated wave). Data of only the I channel which is a real number portion is stored in the preamble buffer 23, so that only data of the I channel is

compared in the multipliers 24a, 24b, ... 24n.

Then, output of the correlation value of the respective multipliers 24a-24n is supplied to an accumulation adder 25, in which electric power level corresponding to 22 symbols are added accumulately and an output of the added values is supplied to a determining portion 26. The determining portion 26 carries out a processing for determining whether the electric power level obtained by accumulated addition is higher or lower than a threshold level set preliminarily. If it is determined that it is higher than the threshold level, its determining output is supplied from a terminal 27 to a reception timing control means (circuit corresponding to a time base controller 211 of FIG. 2) and then, processing timing in the FFT circuit and the like are controlled based on the determined timing. When another time slot in the same packet is subjected to transformation, the transformation processing is carried out cyclically in the period of the modulation time from that determined timing. The principle that correlation detection is carried out with the structure shown in FIG. 11 is the same as that mentioned about the equation [4] in the first embodiment.

By such reception processing, a break of the single modulation time can be determined from reception data prior to Fourier transformation with a simple structure. Only by determining the reception power of any one of the real number portion and imaginary number portion composing the reception

out continuously unlike the above described asynchronous communication, any time slot period may be a time slot in which the preamble signals described in this embodiment are disposed.

Further, it is permissible to change the base band for use upon transmitting the preamble signal depending on a communication state. For example, it is permissible that, when the transmission path state is good, the base band of the time slot for transmitting the preamble signal is in a range of -200 kHz to 200 kHz and when the transmission path state is not good, the base band of the time slot for transmitting the preamble signal is in a range of -100 kHz to 100 kHz. In this case, the detecting circuit for the preamble signal in the reception apparatus may be so constructed to correspond to both the signals.

If the base band of the time slot for transmitting the preamble signal is changed, this can be treated by carrying out a processing shown in FIG. 12, for example, in the symbol expanding portion in the transmission apparatus. That is, after the transmission processing is started (step S101), application band information is obtained from a time base controller in this transmission apparatus (step S102). Next, the symbol stream corresponding to a single modulation time to be transmitted is accumulated in the buffer memory (step S103). Then, it is determined whether or not the frequency of a first symbol position (guard carrier in the above described example) of the

transmission symbol stream is 0 kHz (step S104). This determination can be carried out depending on the application band information obtained in, for example, step S102.

If it is determined that the frequency of the first symbol position is 0 kHz in this determination, the symbol S_{24} to the symbol S_1 are transmitted successively to the IFFT circuit (step S108). After that, the symbol S_1 to the symbol S_{24} are transmitted successively to the IFFT circuit (step S109). Then, with the symbol S_1 set at 0 kHz, the multi-carrier signal in which symbols thereof are expanded symmetrically in a range of -100 kHz to 100 kHz is generated by reverse Fourier transformation and transmitted, and the processing in this time slot is terminated (step S110).

Further, if it is determined that the frequency of the first symbol position is not 0 kHz in step S104, the symbol S_{24} to the symbol S_1 are transmitted successively to the IFFT circuit (step S105) and after waiting in time equivalent to transmission time for about two channels (or transmitting symbol stream corresponding to its application band) (step S106), the symbol S_1 to the symbol S_{24} are transmitted successively to the IFFT circuit (step S107). A multi-carrier signal in which symbols thereof are expanded symmetrically in a range of -200 kHz to 200 kHz as shown in FIG. 10 is generated by reverse Fourier transformation and transmitted, and then, the processing

in this time slot is terminated (step S1110).

In the meantime, the reason why the symbols to be transmitted to the IFFT circuit in step S108 are up to the symbol S_2 while the symbol S_1 is not to be transmitted when symbols are expanded symmetrically in a range of -100 kHz to 100 kHz, is to have the respective symbols to be disposed symmetrically with respect to the position of 0 Hz so that the symbols located at the respective symmetrical positions kill each other.

Although only the slot for transmitting the preamble signals is expanded symmetrically for transmission according to this embodiment, it is permissible to expand symbols symmetrically for transmission in a slot for transmitting other information. Further, information to be disposed in a slot for transmitting other information than the preamble signal may be provided with error correction data before reverse Fourier transformation is carried out. In this case, after Fourier transformation is carried out on the side of the reception apparatus, error correction processing based on error correction data is carried out.

In the processing for detecting the preamble signal within the reception apparatus, its correlation detection processing may be carried out with software as well as with a hardware circuit shown in FIG. 11.

CLAIMS

1. A multi-carrier signal transmission apparatus for transmitting a signal in which first information necessary for gaining synchronism of transmission signal is disposed at a predetermined interval in second information which is the other information, comprising:

data arrangement means for arranging said first information and said second information;

first modulation means for generating transmission symbol stream by modulating data created by said data arrangement means;

symbol generating means for expanding transmission symbol stream generated by said first modulation means on frequency axis so as to generate the transmission symbol stream symmetrical on the frequency axis; and

second modulation means for converting the transmission symbol stream symmetrical on the frequency axis generated on said symbol generating means by reverse Fourier transformation.

2. The multi-carrier signal transmission apparatus according to claim 1 wherein said data arrangement means disposes said first information and said second information alternately.

3. The multi-carrier signal transmission apparatus according to claim 1 wherein with a symbol at said reference frequency position of the transmission symbol stream as the center, said symbol generating means expands respective symbols of said transmission symbol stream other than that symbol symmetrically on the frequency axis.

4. A multi-carrier signal reception apparatus for receiving a multi-carrier signal including first information necessary for gaining synchronism of a transmission signal and second information, comprising:

memory means for memorizing any one of a real number portion and a imaginary number portion in said first information;

delay means for delaying a received symbol stream by a predetermined time;

a filter portion for extracting said first information using a reception symbol stream delayed by said delay means and reception symbol stream not delayed;

a correlator for gaining correlation between output of said filter portion and the first information of the real number portion or imaginary number portion memorized in said memory means; and

determining means for detecting synchronism depending on a peak position of a correlation value of said correlator.

5. The multi-carrier signal reception apparatus according to claim 4 wherein when processing time of a single unit for Fourier-transforming the multi-carrier signal is a single modulation time, a predetermined time to be delayed by said delay means is set at $1/2$ a single modulation time.

6. A multi-carrier signal transmission apparatus for transmitting first information necessary for gaining synchronism of transmission signal and second information which is the other information as the multi-carrier signal, comprising:

first modulation means for generating a transmission symbol stream by said first information and a transmission symbol stream by said second information selectively; and

symmetrical transmission symbol stream generating means in which a transmission symbol stream based on said first information and generated by said first modulation means is a transmission symbol stream expanded symmetrically on a frequency axis with a predetermined frequency position as a reference.

7. The multi-carrier signal transmission apparatus according to claim 6 wherein with a symbol at said reference frequency position of the transmission symbol stream as the center, said first modulation means expands respective symbols of said transmission symbol stream other than that symbol

symmetrically on the frequency axis.

8. A multi-carrier signal reception apparatus for receiving the first information necessary for gaining synchronism of transmission signal and second information which is the other information, comprising:

memory means for memorizing said first information;

a correlator for gaining correlation between the received symbol stream and the first information of a real number portion or imaginary number portion memorized in said memory means; and

determining means for detecting synchronism depending on a peak position of a correlation value of said correlator.


9. The multi-carrier signal reception apparatus according to claim 8 wherein said memory means memorizes only any one of the real number portion and the imaginary number portion in said first information.

ABSTRACT OF THE DISCLOSURE

In transmitting first information necessary for gaining synchronism of transmission signal and second information which is the other information by determining a break of a single modulation unit with a simple structure and processing prior to Fourier transformation on the side receiving a signal transmitted as a multi-carrier signal, a transmission symbol stream is expanded on a frequency axis. With a predetermined frequency position (for example, 0 kHz) as reference, a transmission symbol stream symmetrical is generated on the frequency axis and then, the transmission symbol stream symmetrical on the frequency axis is Fourier-transformed and transmitted.


FIG. 1

FIG. 1




09/807187

FIG. 2




09/807187

FIG. 3




09/807187

FIG. 4




09/807187

FIG. 5



09/807187



09/807187

FIG. 7A




FIG. 7B






FIG. 8




09/807187

FIG. 9




09/807187

FIG. 10




09/807187

FIG. 11



09/807187

FIG. 12



09/807187

DESCRIPTION OF REFERENCE NUMERALS

- 11: input terminal
12: delay circuit
13: adder
14: shift register
15: preamble buffer
16a-16n: multiplier
17: accumulative adder
18: determining portion
19: output terminal
21: input terminal
22: shift register
23: preamble buffer
24a-24n: multiplier
25: accumulative adder
26: determining portion
27: output terminal
100, 100': radio transmission apparatus
101: video circuit
102: voice circuit
103: mixing circuit
104: interleaver
105: modulator
106: reverse fast Fourier transformation circuit (IFFT circuit)
108: transmission processing circuit
109: time base controller
110: antenna

111: symbol expanding circuit
200: radio reception apparatus
201: antenna
202: high frequency portion
203: analog/digital converter
204: window detecting portion
205: fast Fourier transformation circuit (FFT circuit)
206: demodulator
207: deinterleaver
208: viterbi decoder
209: video circuit
210: voice circuit
211: time base controller
D1: first information
D2: second information

S00P1201US00
6640/62669

DECLARATION AND POWER OF ATTORNEY

As a below-named inventor, I hereby declare that:

My residence, post office address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

**MULTI-CARRIER SIGNAL TRANSMITTING APPARATUS AND MULTI-CARRIER
SIGNAL RECEIVING APPARATUS**

specification of which
(check one)

_____ is attached hereto.

 X was filed on April 10, 2001 as _____

International Filing Date August 10, 2000

Application Serial No. 09/807,187

and was amended on _____
(if applicable)

I hereby state that I have reviewed and understand the contents of the above-identified specification, including the claims, as amended by any amendment referred to above.

I acknowledge the duty to disclose information of which I am aware which is material to the examination of this application in accordance with Title 37, Code of Federal Regulations, Section 1.56(a).

I hereby claim foreign priority benefits under Title 35, United States Code, Section 119 of any foreign application(s) for patent or inventor's certificate listed below and have also identified below any foreign application for patent or inventor's certificate having a filing date before that of the application on which priority is claimed:

Prior Foreign Application(s)

Priority Claimed

Number

Country

Filing Date

Yes

No

09607157-082101

Declaration and Power of Attorney

Page 2

I hereby claim the benefit under Title 35, United States Code, Section 120 of any United States Application(s) listed below and, insofar as the subject matter of each of the claims of this application is not disclosed in the prior United States application in the manner provided by the first paragraph of Title 35, United States Code, Section 112, I acknowledge the duty to disclose material information as defined in Title 37, Code of Federal Regulations, Section 1.56(a) which occurred between the filing date of the prior application and the national or PCT international filing date of this application:

<u>Application Serial No.</u>	<u>Filing Date</u>	<u>Status</u>
_____	_____	_____
_____	_____	_____

And I hereby appoint Jay H. Maioli, Reg. No. 27,213; Donald S. Dowden, Reg. No. 20,701; William E. Pelton, Reg. No. 25,702; Peter J. Phillips, Reg. No. 29,691; Gerald W. Griffin, Reg. No. 18,886; Ivan S. Kavrukov, Reg. No. 25,161; Christopher C. Dunham, Reg. No. 22,031; Norman H. Zivin, Reg. No. 25,385; John P. White, Reg. No. 28,678; and Robert D. Katz, Reg. No. 30,141; and each and all of them, all c/o Cooper & Dunham, 1185 Avenue of the Americas, New York, NY 10036 (Tel. (212) 278-0400), my attorneys, each with full power of substitution and revocation, to receive the patent, to transact all business in the Patent and Trademark Office connected therewith and to file any International Applications which are based thereon under the provisions of the Patent Cooperation Treaty.

Please address all communications, and direct all telephone calls, regarding this application to

JAY H. MAIOLI
Cooper & Dunham LLP
1185 Avenue of the Americas
New York, New York 10036
Tel. (212) 278-0400

Reg. No. 27,213

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under Section 1001 of Title 18 of the United States Code and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

Full name of sole or First joint inventor Hideki Iwami
Inventor's signature Hideki Iwami
Citizenship Japanese Date of Signature July. 16. 2001
Residence Saitama, Japan
Post Office Address c/o Sony Corporation, 7-35 Kitashinagawa, 6-Chome
Shinagawa-ku, Tokyo 141, JAPAN